

ICON 4-SPOKE BASE METAL / design Marcello Ziliani
7602, 7604

mara[®]

DESCRIPTION / DESCRIZIONE

en Mara presents the new Icon 4-Spoke base Metal: the lines are now moulded in a polypropylene shell that makes it ideal for office, contract and residential contexts. The detail of the inclined backrest is taken up from the original model to form the armrests, culminating in a moulding that literally embraces the seat. Echoing the armchair, the search for the same ergonomics is concealed in the controlled movement that supports the posture and enhances the comfort of the chair. Icon 4-Spoke base Metal is completed with a soft seat cushion, removable and washable: a decorative and practical accessory that enriches the chair and makes it even more comfortable.



it Mara presenta la nuova Icon 4-Spoke base Metal: le linee sono ora plasmate in una scocca in polipropilene che la rende ideale per i contesti ufficio, contract e residenziali. Della versione originale Soft è ripreso il dettaglio dello schienale inclinato che va a comporre i braccioli, culminanti in una fascia che abbraccia letteralmente la seduta. Fa eco alla poltroncina, la ricerca della medesima ergonomia nascosta nel movimento controllato che asseconda la postura e accresce il comfort di questa seduta a pozzetto. Icon 4-Spoke base Metal si completa con un morbido cuscino per la seduta, removibile e lavabile: un accessorio estetico e pratico, che impreziosisce la sedia e la rende ancora più confortevole.

ICON 4-SPOKE BASE METAL
4 steel legs armchair
poltroncina 4 gambe in metallo

ICON 4-SPOKE BASE METAL
ON CASTORS
4 steel legs armchair,
on castors
poltroncina 4 gambe in metallo, su ruote

7602

7604



fire retardant upholstery
rivestimenti ignifughi



removable upholstery
sfoderabile



outdoor version
versione outdoor



water repellent upholstery
rivestimenti idrorepellenti



1 ICON 4-SPOKE BASE METAL / 7602	5,7 Kg	1 pc 0,18 mc	8 box / EU pallet
1 ICON 4-SPOKE BASE METAL ON CASTORS / 7604	6 Kg	1 pc 0,18 mc	8 box / EU pallet


SHELL / SCOCCA

polypropylene
polipropilene




ACCESSORIES / ACCESSORI

7500CUS



removable soft cushion
morbido cuscino removibile

7500CUS



outdoor removable soft cushion
morbido cuscino removibile per outdoor

ICON 4-SPOKE BASE METAL / design Marcello Ziliani 7602, 7604

mara®

FRAME / STRUTTURA

powder coated steel
acciaio verniciato



296 *
textured
raggrinzato
RAL 9010



301
textured
raggrinzato
RAL 7044



444 *
textured
raggrinzato
RAL 8004



700 *
textured
raggrinzato
RAL 7000



203 *
textured
raggrinzato
RAL 6003



111 *
textured
raggrinzato
RAL 5011



333 *
textured
raggrinzato
RAL 3003



131
textured
raggrinzato
RAL 9006



148 *
textured
raggrinzato
RAL 7016



120 *
textured
raggrinzato
RAL 9005

* available for outdoor version, only for 7602

* disponibile per versione outdoor, solo per 7602



WATER REPELLENT AND FIRE RETARDANT UPHOLSTERIES / RIVESTIMENTI IDROREPELLENTI E IGNIFUGHI



CAT. OUTDOOR, SOLIDS - SUNBRELLA



P101



P106



3983



3988



P104

COMPOSITION / COMPOSIZIONE

100% Sunbrella® Acrylic

WEIGHT / PESO

11.50 OZ. LY. YD.

7.66 OZ.SQ.YD.

FIRE RESISTANCE / RESISTENZA AL FUOCO

NFPA 260:2013, Class: 1 cover fabric;

Meets CA #117-2013 Sec. E (CS-191-53) Classification: 1 Normal Flammability;

DISCLAIMER DOES NOT PASS ASTM E84 FOR PANELS OR NFPA 701 FOR DRAPERY.

CLEANING RULES / NORME DI PULIZIA

All Sunbrella® fabrics are engineered to combine the highest level of design and performance. For easy day-to-day maintenance of your Sunbrella fabric: Brush off loose dirt. Spray on a cleaning solution of water and mild soap. Use a soft bristle brush to clean. Allow cleaning solution to soak into the fabric. Rinse thoroughly until all soap residue is removed. Air dry.


Tutti i tessuti Sunbrella® sono progettati per combinare il massimo livello di design e prestazioni. Per una facile manutenzione quotidiana del tessuto Sunbrella: Spazzolare lo sporco in eccesso. Spruzzare una soluzione detergente di acqua e sapone neutro. Utilizzare una spazzola a setole morbide per pulire. Lasciare che la soluzione detergente penetri nel tessuto e risciacquare accuratamente fino a rimuovere tutti i residui di sapone. Asciugare all'aria.

ICON 4-SPOKE BASE METAL / design Marcello Ziliani 7602, 7604

mara®

FIRE RETARDANT UPHOLSTERIES / RIVESTIMENTI IGNIFUGHI

CAT. C, REMIX 3 - KVADRAT



COMPOSITION / COMPOSIZIONE

90% new wool, 10% nylon

WEIGHT / PESO

420 g/lin.m, 13.6 oz/ly

ABRASION RESISTENCE / RESISTENZA ABRASIONE

100.000 Martindale rubs, EN ISO 12947

TEST IGNIFUGO / TEST IGNIFUGO


AS/NZS 1530.3 • BS 5852 crib 5 with treatment • BS 5852 part 1 • IMO FTP Code 2010 Part 7 with treatment • IMO FTP Code 2010 Part 8 • NF D 60 013 • NFPA 260 • SN 198 898 5.3 with treatment • UNI 9175 1IM • US Cal. Bull. 117-2013 • EN 1021-1/2 • AS/NZS 3837 class 2 • ÖNORM B1/Q1 • ASTM E84 Class A Unadhered • ASTM E84 Class A Adhered • GB 50222 B1 with treatment (Chinese) • EN 13501 B-s2, d0 with treatment

CLEANING RULES / NORME DI PULIZIA

Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid. Disinfection, see kvadrat.dk

Passare spesso l'aspirapolvere, possibilmente ogni settimana. Rimuovere le macchie non appena si formano, con acqua calda pulita o acqua calda o frizzante. Pulire a estrazione quando necessario. La pulizia a estrazione può sciogliere la colla a base d'acqua. Prestare attenzione alla temperatura e alla quantità di liquido detergente. Disinfezione, vedi kvadrat.dk

CAT. C, FIELD 2 - KVADRAT



COMPOSITION / COMPOSIZIONE

100% Trevira CS

WEIGHT / PESO

450 g/lin. m (14.51 oz/ly)

ABRASION RESISTENCE / RESISTENZA ABRASIONE

80.000 Rubs Martindale (EN ISO 12947)

TEST IGNIFUGO / TEST IGNIFUGO

NF D 60 013 • US Cal. Bull. 117-2013 • NFPA 701 • BS 5852 Crib 5 • EN 1021-1/2 • AS/NZS 3837 class 1 • IMO FTP Code 2010 Part 8 • DIN 4102 B1 • NF P 92 507 M1 • FAR 25.853 • UNI 9175 1IM • UNI 9177 Classe 1 • BS 5867 part 2 type B • SN 198 898 5.2 • EN 13501-1, B-s1, d0 • ÖNORM B1/Q1 • CAN ULC S102 • CAN ULC S109 • IMO FTP Code 2010 Part 5 • GB 8624 B1 • ASTM E84 Class A Unadhered

CLEANING RULES / NORME DI PULIZIA

Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid. Disinfection, see kvadrat.dk

Passare spesso l'aspirapolvere, possibilmente ogni settimana. Rimuovere le macchie non appena si formano, con acqua calda pulita o acqua calda o frizzante. Pulire a estrazione quando necessario. La pulizia a estrazione può sciogliere la colla a base d'acqua. Prestare attenzione alla temperatura e alla quantità di liquido detergente. Disinfezione, vedi kvadrat.dk

ICON 4-SPOKE BASE METAL / design Marcello Ziliani
7602, 7604

mara[®]

CAT. C, CAPTURE - GABRIEL



3001



3601



3701



3801



4601



5101



6601



7401

COMPOSITION / COMPOSIZIONE

85% New Zealand wool, 15% Polyamide

WEIGHT / PESO

475 g/lm — 15.32 oz/lin.yd

ABRASION RESISTANCE / RESISTENZA ABRASIONE

200,000 — rubs martindale (EN ISO 12947-2)

200,000 — rubs martindale (ASTM D4966) (heavy duty upholstery)

TEST IGNIFUGO / TEST IGNIFUGO

BS EN 1021 1&2 Cigarette and Match • BS 5852 Part 1 0,1 Cigarette & Match, The Furniture and Furnishing Regulations 1988 • Class Uno UNI 9175 Class 1 I EMME • CA TB 117-2013 • ASTM E 84 Class 1

FIRE RETARDANT UPHOLSTERIES / RIVESTIMENTI

IGNIFUGHI

CAT. C, CAPTURE - GABRIEL

4601 5101 6601 7401

3001 3601 3701 3801

CLEANING RULES / NORME DI PULIZIA

Always follow the manufacturer's instructions and finish by wiping with a damp cloth.

Seguire sempre le istruzioni del produttore e finire con un panno umido.

CAT. B, FENICE - PUGI



601



602



603



452



301



505

COMPOSITION / COMPOSIZIONE

75% WO 25% PA

WEIGHT / PESO

335 ± 7% / 500 ± 7% gr./m²-gr./mtl.

ABRASION RESISTANCE / RESISTENZA ABRASIONE

100.000 ± 20% cicli (UNI EN ISO 12947)

CERTIFICATIONS / CERTIFICAZIONI

Misura del coefficiente di assorbimento acustico UNI EN ISO 354:2003 • Rapporto di misura del coeff. di assorbimento acustico UNI EN ISO 10534-2 • Rapp.di Prova Classe 1IM-

con schiuma standard ignifuga con densità 25 kg³ • BS 5852 Crib N°5 with standard Foam 20/22 Kg/cu.m-CON TRATT. A RICHIESTA • EN 1021 Part 1-2 using a standard Foam 20/22 Kg/cu.m. • Calif.Bull.117 June 2013

CLEANING RULES / NORME DI PULIZIA


Vacuum regularly with a smooth nozzle, without brushing.

Usare con regolarità l'aspirapolvere a beccuccio liscio, senza spazzolare.

ICON 4-SPOKE BASE METAL / design Marcello Ziliani
7602, 7604

mara[®]

CAT. B, STEP MELANGE - GABRIEL 



COMPOSITION / COMPOSIZIONE

100% Trevira cs

WEIGHT / PESO

470 g/lm, 15,16 oz/lin.yd

ABRASION RESISTENCE / RESISTENZA ABRASIONE

100.000 rubs martindale (EN ISO 12947-2), 100,000 double rubs wyzenbeek (ASTM D4157-07) (heavy duty upholstery)

FIRE RESISTANCE / RESISTENZA AL FUOCO


DIN 4102 - B1 • NFP 92-503/504/505 M1 • BS EN 1021 1&2 Cigarette and Match • BS EN 1021-1 Cigarette • BS 5852 Crib 5 • ÖNORM A3800-B1-B3825-Q1 UK • FAR/JAR 25.853 (a) (i) (ii) • AM 18 - NF D 60-013-(only for fabric) • CA TB 117-2013 • Class Uno UNI 9175 Class 1 I EMME • DIN EN 13501-1 B-s1,d0 • IMO MSC 307(88) Annex 1 part 8 • MED Certificate IMO • IMO MSC 307(88) Annex 1 part 8 UK • MED Certificate IMO UK • CAN/ULC-S102.2 • CAN/ULC-S 109

CLEANING RULES / NORME DI PULIZIA

Step Melange is made of Trevira CS which is a polyester material suited for environments with special requirements for cleaning. Can be wiped with Virkon S, Actichlor Plus, Prime Source ren-93 or Ethanol (70-85%). Always follow the manufacturer's instructions and finish by wiping with a damp cloth.

Step Melange è realizzato in Trevira CS, un materiale in poliestere adatto ad ambienti con particolari esigenze di pulizia. Può essere pulito con Virkon S, Actichlor Plus, Prime Source ren-93 o etanolo (70-85%). Seguire sempre le istruzioni del produttore e finire con un panno umido.

CAT. A, MIRAGE - PUGI 



COMPOSITION / COMPOSIZIONE

100% PL FR (Tr Cs)

WEIGHT / PESO

330 ± 10% / 460 ± 10% gr./m²-gr./mtl.

ABRASION RESISTENCE / RESISTENZA ABRASIONE

100.000 ± 20% cicli (UNI EN ISO 12947:2000)

CERTIFICATIONS / CERTIFICAZIONI

Rapporto di misura della resistenza al flusso d'aria secondo la norma ISO 9053-2 • Classe 1 Sipari, Drappeggi, Tendaggi Classe 1 IM - Rapporto di prova • EN ISO 6940/6941: BS 5852 Crib N°5 using a CM Foam 35 Kg/cu.m. • B1 DIN 4102. • EN

1021 Part 1-2 using a CM Foam 35 Kg/cu.m. • EN 13773 Burning Behaviour: Class 1 • EN 13501-1 esp 1,2 : B-s1, • Calif.Bull.117 June 2013 • Fire Protection Classification: 5.3 • M1 + NF D 60-013:2006 AM18 • FAR.25853 Classification: yes • B1 - OENORM 3800 PART 1 + OENORM B3825 • Azimut • MED/3.19 MED/3.21: Draperies, Curtains and Bedding comp • MED annex A.1 item:A.1/3.20 Upholstered Furniture

CLEANING RULES / NORME DI PULIZIA

Vacuum regularly with a smooth nozzle, without brushing.

Usare con regolarità l'aspirapolvere a beccuccio liscio, senza spazzolare.

ICON 4-SPOKE BASE METAL / design Marcello Ziliani
7602, 7604

mara[®]

CAT. A, ECO-LEATHER GAZEBO - LEDERPLAST



06



151



1194



6986



4981



726



991

COMPOSITION / COMPOSIZIONE

87,5 % P.V.C. Plastificato, 8,1 % Poliestere, 4,4 % Cotone

WEIGHT / PESO

640 ± 50 g/m2 (UNI EN 2286-2:2001)

ABRASION RESISTENCE / RESISTENZA ABRASIONE

300.000 cicli (UNI EN ISO 5470-2: 2004)

FIRE RESISTANCE / RESISTENZA AL FUOCO

UNI 9175: 2010 Reaction ignition of upholstered furniture exposed to a small flame CLASS 1 IM • BS 1021-1: 2014 Assessment of the ignitability of upholstered furniture – Part 1: Ignition source smouldering cigarette • BS 1021-1: 2014 Assessment of the ignitability of upholstered furniture – Part 2: Ignition source match flame equivalent • BS 5852 parte

1: 1979 Match flame equivalent test • The material complies with the requirements of BS 7176: 2007+A1: 2011 for the hazard category LOW HAZARD • California Technical Bulletin 117:2013 • IMO Resolution MSC.307(88) - FTP CODE 2010 – PART 8 • AFNOR NF P 92 503 – M2 • ISO 3795: 1989 • FAR 25.853 Part 25 Appendix F Vertical test Par (a) (1) (ii)

CLEANING RULES / NORME DI PULIZIA

Clean with damp soapy cloth and rinse well with clean water. Do not use solvents, bleaches, synthetic detergents, polishes or aerosol spray.

Pulire con tessuto inumidito ed insaponato e sciacquare bene con acqua pulita. Non usare solventi, candeggine e detergenti chimici o spray per lucidare.



en All the energy used in our company is 100% green and comes exclusively from renewable sources.

it Tutta l'energia utilizzata nella nostra azienda è 100% GREEN e proviene esclusivamente da fonti rinnovabili.

en As it is always seeking to improve its products, the company reserves the right to modify or upgrade the products without prior notice, at any time. Colors should be considered purely indicative. Mara's Collections are worldwide protected by the industrial property right and patents.

it Mara, sempre alla ricerca del miglioramento dei propri prodotti, si riserva la facoltà di apportare modifiche costruttive e funzionali in qualsiasi momento senza alcun preavviso. I colori dei materiali sono da ritenersi puramente indicativi. Tutte le collezioni Mara sono protette nel mondo dal diritto di proprietà industriale e da brevetti registrati.